

Recirculating Chiller ProfiCool *Minimus*

- Single-circuit system including tank open to atmosphere
- Maintenance-free air-cooled refrigeration machine
- Plastic tank with water level indicator
- Electronic microprocessor-controlled thermostat with digital display (LED)
- Built-in pump (see pump characteristics)
- Housing powder-coated, bicolour (blue/white)
- Construction using evaporator coils provides effective protection against freezing
- Extremely quiet



ProfiCool *Minimus*

Model ProfiCool <i>Minimus</i>	PCMin 04.02	PCMin 06.02
Net cooling capacity at +20°C/+15°C watts	: 350/310	500/450
Operating range *	°C : +5 / +25	+5 / +25
Pump	type : P1-KA14D	P1-KA14D
Pump capacity	l/min : 12.5	12.5
Pump pressure	bar : 0.75	0.75
Tank capacity	litres : 7	7
Water connection (quick connection)	: for hose 10 mm outside diameter	
Power input max.	kW : 0.35	0.47
Operating Voltage	Volts/Hz/Phase : 230/50-60/1	230/50-60/1
Weight	kgs : 22	25
Dimensions WxDxH	mm : 413x283x415	413x283x415
Refrigerant	CFC-free : R134a	R134a

* Set Temperatures <+5°C and >+25°C on request.

ProfiCool *Minimus* + options / accessories: Cat. No.

ProfiCool Minimus PCMin 04.02-NED	GUPCMin04.02-NED
ProfiCool Minimus PCMin 06.02-NED	GUPCMin06.02-NED
Pump P1-KA15D instead of P1-KA14D	MPCMin6-P1-KA15D

Additional accessories as well as pump alternatives on request.

